




BLU 60 mm

DESCRIPTION: Slab **TEXTURE:** Smooth and HD² smooth

PALLET OVERVIEW



NOTES

See page 26 to 28 for more technical information. When used in a permeable pavement application, see page 93 to 100 for more technical information.

See page 20 for more information about applications.

JOINT WIDTH: 9/32" (7 mm)
% OF SURFACE OPENING: 4.5%**
INFILTRATION RATE: 570 in./hr (14 475 mm/hr)


*For this application, it is recommended that this product be installed on a concrete base as designed by a local Engineer.

**For permeable application, the installation should be combined with Blu 6x13 in a modular pattern. A min. of 4.5% opening surface requires 75% of Blu 6x13 and 25% of Blu.


Specifications per pallet	Imperial	Metric
Cubing	116.82 ft²	10.96 m ²
Approx. Weight Smooth	3 170 lbs	1 438 kg
Approx. Weight HD ² Smooth	3 295 lbs	1 495 kg
Number of rows	11	
Coverage per row	10.62 ft ²	0.99 m ²
Linear coverage per row	9.81 lin. ft	3.02 lin. m

Unit dimensions	in	mm	Units/pallet
A (Smooth)	Height: 2 3/8	60	44 units
	Width: 13	330	
	Length: 6 1/2	165	
B (HD ² Smooth)	Height: 2 3/8	60	44 units
	Width: 13	330	
	Length: 13	330	
C (Smooth)	Height: 2 3/8	60	22 units
	Width: 13	330	
	Length: 19 1/2	495	


01 | Modular pattern



02 | Modular pattern



03 | Linear pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

